

TO-92 NPN Silicon NPN transistor in a TO-92 Plastic Package.





h_{FE}
High breakdown voltage, excellent linearity of h_{FE} and small C_{ob} , fast switching speed.

60
High voltage switching. AF 60W pre-driver applications.




PIN1 Base PIN 2

/ Electrical Characteristic Curve



/ Marking Instructions



BR:

C2909

R: h_{FE}

Note:


BR: Company Code.

C2909: Product Type.

R: h_{FE} Classifications Symbol.

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



- | | | | | | | |
|---|-------|-----|-----------|--------|---|--------------------------------------|
| 1 | 25 | 150 | 60 | 90sec; | Note: | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | | 2.Peak Temp.:255±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. | |

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp:270±5 Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units	Dimension	(unit mm3)
--------------	-------	-----------	------------