

SOT-323 NPN Silicon NPN transistor in a SOT-323 Plastic Package.

Low noise and high power gain.

low noise amplifier at VHF, UHF and CATV band applications.




PIN1 Emitter PIN 2 Base PIN 3 Collector

h_{FE} Classifications Symbol	Q	R	S	T
h_{FE} Range	50 100	80 160	125 250	200 330
Marking	HR23	HR24	HR25	HR26


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	20	V
Collector to Emitter Voltage	V_{CEO}	12	V
Emitter to Base Voltage	V_{EBO}	3.0	V
Collector Current - Continuous	I_C	100	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	


Storage Temperature Range: -55 150



SOT-323

单位: mm





H


R23

Note:

H: Company Code.

R23: Product Type.

K\d g\iXk i\`Gif]`d`]fi`@`l`]f n`Jf d` \i`e`^ZGY\$=i\`z



Note:

- | | | | | | |
|---|-------|-----|-------|----------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | 5±0.5 | sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205