

/ Descriptions

TO-220 NPN Silicon NPN transistor in a TO-220 Plastic Package.


/ Features

Low collector-to-emitter saturation voltage.


/ Applications

Humidifier, DC-DC converter, and general purpose.

/ Equivalent Circuit



/ Pinning




PIN1 Base PIN 2 Collector PIN 3 Emitter


/ h_{FE} Classifications & Marking

See Marking Instructions.


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



BR

C3834

Note:

BR: Company Code

C3834: Product Type.

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



- | | | | | | | |
|---|-------|-----|-----------|--------|---|--------------------------------------|
| 1 | 25 | 150 | 60 | 90sec; | Note: | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | | 2.Peak Temp.:255±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 /sec. | | 3. Cooling Speed: 2~10 /sec. | |

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp.:270±5 Time:10±1 sec


/ Packaging SPEC.

/ BULK

Package Type	Units			Dimension	(unit mm ³)
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /		

/ Notices

3MHZ



- 1 3.0MHZ
- 2 40V
- 3 45W
- 4 HFE 60-70,70-80,80-90

- 1 HFE HFE 60-70 70-80 80-90
- 2 HFE

- 1 Y
- 2