

**/ Descriptions**

TO-220F          NPN          Silicon NPN transistor in a TO-220F Plastic Package.

**/ Features**

High  $V_{CEO}$ , low  $V_{CE(sat)}$ .

**/ Applications**

Power out amplifier applications.

**/ Equivalent Circuit**



**/ Pinning**



PIN1 Base          PIN 2 Collector          PIN 3 Emitter

**/  $h_{FE}$  Classifications & Marking**

$h_{FE}$ Classifications Symbol	R	O
$h_{FE}$ Range	60 120	100 200

**/ Absolute Maximum Ratings(Ta=25 )**


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	$V_{CBO}$	100	V
Collector to Emitter Voltage	$V_{CEO}$	100	V
Emitter to Base Voltage	$V_{EBO}$	5.0	V
Collector Current - Continuous	$I_C$	5.0	A
Collector Power Dissipation	$P_C$	2.0	W
Collector Power Dissipation	$P_C(T_C=25 )$	40	W
Junction Temperature	$T_j$	150	
Storage Temperature Range	$T_{stg}$	-55 150	

**/ Electrical Characteristics(Ta=25 )**

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	$I_{CBO}$	$V_{CB}=100V$ $I_E=0$			20	A
Emitter Cut-Off Current	$I_{EBO}$	$V_{EB}=5.0V$ $I_C=0$			20	A
DC Current Gain*	$h_{FE}$	$V_{CE}=5.0V$ $I_C=1.0A^*$	60		200	
Collector to Emitter Saturation Voltage*	$V_{CE(sat)}$	$I_C=3.0A$ $I_B=0.3A^*$			1.0	V
Transition Frequency	$f_T$	$V_{CE}=5.0V$ $I_C=500mA$ $f=1.0MHz$	10			MHz


\*: /pulse test.

/ Electrical Characteristic Curve





/ Marking Instructions



BR

D2603

R:  $h_{FE}$

\*\*\*\*

Note:

BR: Company Code.

D2603: Product Type.

R:  $h_{FE}$  Classifications Symbol

\*\*\*\*: Lot No. Code, code change with Lot No.

