

# BR2SB1260Q

Rev.A Apr.-2023

JF K\$/O

GE G`

Silicon PNP transistor in a SOT-89 Plastic Package.



9I )J; (/O/H

8<: \$H(' (

High breakdown voltage, good  $h_{FE}$  linearity, low  $V_{CE(sat)}$ , complements the BR2SD1898Q, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

General power amplifier applications, Meet the stringent requirements of automotive applications.

## / Equivalent Circuit



PIN1 Base

PIN 2 Collector

PIN 3 Emitter

# BR2SB1260Q







Rev.A Apr.-2023

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	$V_{CBO}$	-80	V
Collector to Emitter Voltage	$V_{CEO}$	-80	V
Emitter to Base Voltage	$V_{EBO}$	-5.0	V
Collector Current-Continuous	$I_C$	-1.0	A
Collector Current-Continuous(Pulse)	$*I_{CP}$	-2.0	A
Collector Power Dissipation	$**P_C$	0.5	W
	$*P_C$	2.0	W
Junction Temperature	$T_j$	150	
Storage Temperature Range	$T_{stg}$	-55 150	

\*Single pulse  $P_w=100ms$  100ms  
\*\*mounted on 40x40x0.7mm ceramic board 40x40x0.7m

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	$V_{CBO}$	$I_C=-50\mu A$ $I_E=0$	-80			V
Collector to Emitter Breakdown Voltage	$V_{CEO}$	$I_C=-1.0mA$ $I_B=0$	-80			V

/ Electrical Characteristic Curve




**BR2SB1260Q**

Rev.A Apr.-2023

**DATA SHEET**

/ Marking Instructions



H

BH

P h<sub>FE</sub>

!!

Note:

Q: Automobile halogen-free product Code

BH: Product Type

P h<sub>FE</sub> Classifications Symbol

\*\* : Lot No. Code, code change with Lot No

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)


Note:

- 1            150 ~ 200            60 ~ 120sec;      1.Preheating:150~200 , Time:60~120sec.
- 2            255..5                      5..0.5sec;      2.Peak Temp.:255..5 , Duration:5..0.5sec.
- 3                              2 ~ 10 /sec.      3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260..5                      10..1 sec.                      Temp.:260±5                      Time:10±1 sec