

Q/Parameter


N/Symbol

Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Over temperature protection						
Over-temperature protection	OTP			145		
Over-temperature protection release temperature	OTPR			120		
Detection delay						
Overcharge Voltage Detection Delay Time	T _{OCV}			100		ms
Overdischarge Voltage Detection Delay Time	T _{ODV}			100		ms
Overdischarge Current1 Detection Delay Time	T _{IOV1}			8		ms
Overdischarge Current2 Detection Delay Time	T _{IOV2}			2		ms
Load Short-Circuiting Detection Delay Time	T _{SHORT}			150		μs

* (OTP) χ τ 5 Ō ≠ ó α η □ ý 6 OTPR ī 3 α 5 Ō
ñ ⚙ ⚙
* ī ī ⚙ χ ⚙ ~ ī ī ⚙ ā W□ ī ⚙ 3 3 α J □
τ ⚙

FunctionI Block Diagram



/ Charger Detection

E ̈́ ♂ ↑ ̃ ï [0B] ♂ - ♂ ' VVP 1 Ů ♂ η ν ♂ ₅ ♪ ♂ +V_{FKD}, E ♂ -


♂ ν ̈́ ₅ ♪ ♂ +V_{RGV}, EUF06453FZV ̈́ ̈́ ♂ ↑ ̃

0V / 0V Battery Charging Function

3V Ɔ Ɔ - Ɔ H 516V Ɔ Ɔ Q ^ † ð % H P R V Ă Ă Ɔ Q || 1 Ɔ
Ɔ - Ɔ H 516V Ɔ Ɔ ℒ j Ĩ 533 pD Ɔ - Ɔ Q "Ω


/ Timing Chart

→ → / Overcharge → Discharge → Normal Operation.




/ Timing Chart

→ / Overdischarge → Charging → Normal Operation.



/ Timing Chart

→ / Discharge Overcurrent → Normal Operation.



BRCL3120CZV

Rev.A Feb.-2026

DATA SHEET

