

# BRCS020N10SHTL

Rev.A Mar.-2025

## / Descriptions

TOLL-8L N

N-Channel MOSFET in a TOLL-8L Plastic Package .

## / Features

$V_{DS}(V)=100V$   $I_D=259A$

$R_{DS(ON)}@10V$  2.0m (Typ. 1.6m )


HF Product.

## / Applications


DC/DC

DC/DC converter,Power switch,Motor drives.

## / Equivalent Circuit



## / Pinning



PIN1 G PIN2 3 4 5 6 7 8 S PIN9 D

## / Marking

See Marking Instructions.

/ Absolute Maximum Ratings( $T_C=25$  )

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		$V_{DS}$	100	V
Drain Current - Continuous		$I_D$	259	A
Drain Current – Pulsed		$I_{DM}$	1036	A
Gate-Source Voltage		$V_{GS}$	$\pm 20$	V
Power Dissipation		$P_{tot}$	250	W
Single Pulse Avalanche Energy( $V_{DD}=50V, L=0.1mH$ )		$E_{AS}$	205	mJ
Junction and Storage Temperature Range		$T_j, T_{stg}$	-55 to 150	
Thermal resistance, junction - ambient	Steady-State	$R_{JA}$	40	/ W
Thermal resistance, junction - case	Steady-State	$R_{JC}$	0.5	

/ Electrical Characteristics( $T_a=25$  )

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$BV_{DSS}$	$I_D=250\mu A, V_{GS}=0V$	100			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=100V, V_{GS}=0V$			1	$\mu A$
Gate-Body leakage current	$I_{GSS}$	$V_{DS}=0V, V_{GS}=\pm 20V$			$\pm 100$	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2.2	3.0	3.8	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=100A$		1.6	2.0	m
Diode Forward Voltage	$V_{SD}$	$I_S=100A, V_{GS}=0V$		0.9	1.2	V
Gate Resistance	$R_g$	$f=1.0MHz$		1.2		
Input Capacitance	$C_{iss}$	$V_{DS}=50V, V_{GS}=0V, f=1.0MHz$		10120		pF
Output Capacitance	$C_{oss}$			1360		
Reverse Transfer Capacitance	$C_{rss}$			50		
Total Gate Charge	$Q_g$	$V_{GS}=10V, I_{DS}=100A, V_{DS}=50V$		176		nC
Gate Source Charge	$Q_{gs}$			47		
Gate Drain Charge	$Q_{gd}$			54		

# BRCS020N10SHTL

Rev.A Mar.-2025




DATA SHEET

5 786.14 cm/lm1 D09596 -1.3886 T


Parameter	Symbol	Test Conditions
-----------	--------	-----------------

/ Electrical Characteristic Curve




**Figure 1: On-Region Characteristics**

**Figure 2: Transfer Characteristics**



**Figure 3: On-Resistance vs. Drain Current and Gate Voltage**

**Figure 4: On-Resistance vs. Junction Temperature**



**Figure 5: On-Resistance vs. Gate-Source Voltage**

**Figure 6: Body-Diode Characteristics**

**Figure 5: O**

/ Electrical Characteristic Curve








Figure 10: Single Pulse Forward Biasing Characteristics


Figure 11: Normalized  $V_{GS(th)}$  vs. Junction Temperature

Figure 12: Normalized  $V_{(BR)DSS}$  vs. Junction Temperature

/ Electrical Characteristic Curve




**/ Package Dimensions**



Symbol	Dimensions In Millimeters			Symbol	Dimensions In Millimeters		
	MIN.	NOM.	MAX.		MIN.	NOM.	MAX.
A	2.200	2.300	2.400	b1	9.700	9.800	9.900
c	0.492	0.500	0.508	b1	0.420	0.460	0.500
D	10.280	10.380	10.480	b3	0.350		
E	9.800	9.900	10.000	b4	0.600		
e	1.20 BSC			b5	3.100		
H	11.580	11.680	11.780	b6	1.200		
H1	6.650	6.750	6.850	L	1.700	1.900	2.100
H2	7.300			L1	0.700		
H3	3.200			L2	0.600 5		

## / Marking Instructions



BR

020N10SH

\*\*\*\*

Note

BR                    Company Code

020N10SH        Product Type Code

\*\*\*\*:              Lot No. Code, code change with Lot No.

