

BRCS1C0P06MCQ

Rev.B Aug.-2025

5 é / Descriptions

SOT23-3 .> // x P 3 « | • 'ož

6 CHANNEL MOSFET in a SOT23 -3 Plastic Package.

□^a / Features

$V_{DS} = -60V$; $I_D = -3A$

$R_{DS(on)1@-10V} 0.100m\Omega$ (Type.83m Ω)

$R_{DS(on)2@-4.5V} 0.130m\Omega$ (Type.100m Ω)

... ` ' +) 7 ö Ö ä U ´ Å } L k —) í D } ož


Qualified to AEC-Q101 Standards for High Reliability, HF Product.

Đ ÷ / Applications


6 = 3 • ħ ú • ¼ k á V ñ • } Lož

PWM application & Load switch, Meet the stringent requirements of automotive applications.

Ã W] Ô • / Equivalent Circuit



• Ů - æ / Pinning



PIN1 y G

PIN 2 y S




PIN 3 y D

, M V / Marking

• - ~^a ¢ ož

See Marking Instructions.



Electrical Characteristic Curve




eristics Figure 5: On-Resistance vs. Gate-Source Voltage

Figure 6: Body-Diode Character

Electrical Characteristic Curve




Ø □ =) ⌀ / Package Dimensions



Unit: mm

Dimension

, M y f / Marking Instructions



^a ϕ y
7 y V ñ —) í D } ö æ
C1 y

šWD t...•Ž¢ (x/) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6

^a¢y

Note:

- 1o• Ä½ “† 150½200 - kž• 60½120sec;

2o• Q> “† 255 r5 - kž• 4 Ò 5 r0.5sec;

3o•D N ò i Ò 0 ,† 2½10 - /sec.
- 1.Preheating:150~200 - , Time:60~120sec.

2.Peak Temp.:255 r5 - , Duration:5 r0.5sec.

3.Cooling Speed: 2~10 - /sec.

ÂD /Cã p ¯ »] / Resistance to Soldering Heat Test Conditions

“†y 260 r5 - ž•y 10 r1 sec. Temp.:260±5 Time:10±1 sec

á!De %oY™ á À ì ' Ê "• ÁfCÐ AHyfqt y