

SOP-8 P MOS

P-Channel Enhancement Mode Field Effect Transistor in a SOP-8 Plastic Package.

$V_{DS} (V) = -30V$



$I_D = -8.8 A$

$R_{DS(ON)} < 23m (V_{GS} = -10V)$

$R_{DS(ON)} < 35m (V_{GS} = -4.5V)$

HF Product.

Power Management in Notebook computer, Portable Equipment and Battery powered systems.




PIN 1	S	PIN 2	S	PIN 3	S	PIN 4	G
PIN 5	D	PIN 6	D	PIN 7	D	PIN 8	D


See Marking Instructions.


Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DSS}$	-30	V
Gate-Source Voltage	$V_{GSS}$	$\pm 20$	V
Continuous Drain Current <sup>A</sup>	$I_D (T_a=25^\circ\text{C})$	-8.8	A
Continuous Drain Current <sup>A</sup>	$I_D (T_a=70^\circ\text{C})$	-7.0	A
Pulsed Drain Current <sup>B</sup>	$I_{DM}$	-50	A
Power Dissipation for Single Operation <sup>A</sup>	$P_D (T_a=25^\circ\text{C})$	2.5	W
Power Dissipation for Single Operation <sup>A</sup>	$P_D (T_a=70^\circ\text{C})$	1.2	W
Avalanche Current	$I_{AR}$	-20	A
Repetitive avalanche energy 0.3mH <sup>B</sup>	$E_{AR}$	50	mJ
Maximum Junction Temperature	$T_j$	150	


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$BV_{DSS}$	$I_D=-250\mu A$ $V_{GS}=0V$	-30			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=-30V$ $V_{GS}=0V$			-1.0	$\mu A$
		$V_{DS}=-30V$ $V_{GS}=0V$ $T_J=55^\circ C$			-5.0	
Gate-Body leakage current	$I_{GSS}$	$V_{DS}=0V$ $V_{GS}=\pm 20V$			$\pm 100$	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=-250\mu A$	-1.0	-1.7	-3.0	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=-10V$ $I_D=-8.8A$		18	23	m
		$V_{GS}=-10V$ $I_D=-8.8A$ $T_J=125^\circ C$		25	32	
		$V_{GS}=-4.5V$ $I_D=-6.7A$		27	35	
Forward Transconductance	$g_{FS}$	$V_{DS}=-5V$ $I_D=-8.8A$		12		S
Diode Forward Voltage	$V_{SD}$	$I_S=-2.1A$ $V_{GS}=0V$		-0.73	-1.2	V
Maximum Body-Diode Continuous Current	$I_S$				-2.1	A
Total Gate Charge	$Q_g$	$V_{GS}=-5V$ $V_{DS}=-15V$ $I_D=-8.8A$		17	24	nC
Gate-Source Charge	$Q_{gs}$			5		
Gate-Drain Charge	$Q_{gd}$			6		
Input Capacitance	$C_{iss}$	$V_{GS}=0V$ $V_{DS}=-15V$ $f=1MHz$		1604		pF
Output Capacitance	$C_{oss}$			408		
Reverse Transfer Capacitance	$C_{rss}$			202		
Turn-on Delay Time	$t_{d(ON)}$	$V_{GS}=-10V$ $V_{DS}=-15V$ $I_D=-1A$ $R_{GEN}=6$		13	23	ns
Turn-on Rise Time	$t_r$			13.5	24	
Turn-off Delay Time	$t_{d(OFF)}$			42	68	
Turn-off Fall Time	$t_f$			25	40	











BR

4435


\*\*\*\*

Note:

BR: Company Code

4435: Product Type Code

\*\*\*\*: Lot No. Code, code change with Lot No



Note:

- |   |       |     |       |          |   |
|---|-------|-----|-------|----------|---|
| 1 | 150   | 180 | 60    | 90sec;   | 1.Preheating:150~180 , Time:60~90sec.   |
| 2 | 245±5 |     | 5±0.5 | sec;     | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 |       |     | 2     | 10 /sec. | 3. Cooling Speed: 2~10 /sec.            |

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type	Units					Dimension (unit mm <sup>3</sup> )		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOP/ESOP-8	4,000	2	8,000	6	48,000	13 ×12	360×360×50	380×335×366