






## / Absolute Maximum Ratings(Ta=25 )

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DSS}$	650	V
Drain Current	$I_D(T_c=25)$	7.0	A
Drain Current	$I_D(T_c=100)$	4.4	A
Drain Current - Pulsed	$I_{DM}$	28	A
Gate-Source Voltage	$V_{GSS}$	$\pm 30$	V
Single Pulsed Avalanche Energy	$E_{AS}$	425	mJ
Avalanche Current	$I_{AR}$	9.9	A
Power Dissipation	$P_D(T_c=25)$	100	W
Operating and Storage Temperature Range	$T_j, T_{stg}$	-55 to 150	
Junction to Ambient	$R_{JA}$	110	/W
Junction to Case	$R_{JC}$	1.25	/W

## / Electrical Characteristics(Ta=25 )

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V$ $I_D=250\mu A$	650	690		V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=650V$ $V_{GS}=0V$			1.0	$\mu A$
Gate-Body Leakage Current Forward	$I_{GSS}$	$V_{GS}=\pm 30V$ $V_{DS}=0V$			$\pm 100$	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	2.0	3.2	4.0	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=3.5A$		1.1	1.5	
Input Capacitance	$C_{iss}$	$V_{DS}=25V$ $V_{GS}=0V$ $f=1.0MHz$		1000		pF
Output Capacitance	$C_{oss}$			180		
Reverse Transfer Capacitance	$C_{rss}$			4		
Total Gate Charge	$Q_G$	$V_{DS}=520V$ , $I_D=7.0A$ , $V_{GS}=10V$		30		nC
Gate-Source Charge	$Q_{GS}$			10		
Gate-Drain Charge	$Q_{GD}$			21		
Turn-On Delay Time	$t_{d(on)}$	$V_{DD}=325V$ $I_D=7.0A$ $R_G=25$ $V_{GS}=10V$		52		ns
Turn-On Rise Time	$t_r$			160		
Turn-Off Delay Time	$t_{d(off)}$			400		
Turn-Off Fall Time	$t_f$			190		
Drain-Source Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V$ , $I_S=7.0A$			1.4	V


**/ Electrical Characteristic Curve**



# **BRD7N65S**

Rev.A Dec.-2023

**/ Marking Instructions**



BR

7N65S

!!!!

Note:

BR: Company Code

7N65S: Product Type Code

\*\*\*\*: Lot No. Code, code change with Lot No

(    ) / Temperature Profile for IR Reflow Soldering(Pb-Free)


- |   |        |     |            |        |                                                |
|---|--------|-----|------------|--------|------------------------------------------------|
| 1 | 150    | 180 | 60         | 90sec; | Note:<br>1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245..5 |     | 5..0.5sec; |        | 2.Peak Temp.:245..5 , Duration:5..0.5sec.      |
| 3 |        | 2   | 10         | /sec.  | 3. Cooling Speed: 2~10 /sec.                   |

/ Resistance to Soldering Heat Test Conditions

605..5