

Rev.A Aug.-2022

TO-220F            N  
N-CHANNEL MOSFET in a TO-220F Plastic Package.

Low gate charge, low crss, fast switching.

DC/DC ,

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DSS}$	650	V
Drain Current	$I_D(T_C=25^\circ\text{C})$	5	A
	$I_D(T_C=100^\circ\text{C})$	3.3	A
Drain Current - Pulsed	$I_{DM}$	16	A
Gate-Source Voltage	$V_{GS}$	$\pm 30$	V
Single Pulsed Avalanche Energy(L=10mH)	$E_{AS}$	176	mJ
Avalanche Current	$I_{AS}$	6.3	A
Power Dissipation	$P_D(T_C=25^\circ\text{C})$	28	W
Operating and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	
Junction-to-Ambient	$R_{JA}$	65	/W
Junction-to-Case	$R_{JC}$	4.5	/W


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V$ $I_D=250\mu A$	650			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=650V$ $V_{GS}=0V$			1.0	$\mu A$
Gate-Body Leakage Current, Forward	$I_{GSS}$	$V_{GS}=\pm 30V$			$\pm 100$	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	2	3.3	4	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=2.5A$		1.35	1.5	
Drain-Source Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V$ $I_{SD}=1A$ $T_J=25$			1.2	V
Gate Resistance	$R_g$	$V_{GS}=0V$ $f=1.0MHz$		4.1		
Input Capacitance	$C_{iss}$	$V_{DS}=25V$ $V_{GS}=0V$ $f=1.0MHz$		585		pF
Output Capacitance	$C_{oss}$			190		pF
Reverse Transfer Capacitance	$C_{rss}$			23		pF
Turn-On Delay Time	$t_{d(on)}$	$V_{DS}=250V$ $I_D=5A$ $R_G=25$ $V_{GS}=10V$		15		ns
Turn-On Rise Time	$t_r$			32		ns
Turn-Off Delay Time	$t_{d(off)}$			35		ns
Turn-Off Fall Time	$t_f$			25		ns











BR  
5N50  
\*\*\*\*

Note:

BR: Company Code

5N50: Product Type

\*\*\*\*: Lot No. Code, code change with Lot No

Rev.A Aug.-2022