

5 é / Descriptions

: 5 .> // x RK Ô Â 8 â ' k J • ° % Àož

Schottky Barrier Diode in a TO-220 Plastic Package, Adopt new mold.

□^a / Features

C ô z k | ä ä k —)í D }ož

Low power loss, high efficiency, HF product.

Đ ÷ / Applications

9 ä È• z 9o• Ý v ... v 8 â ' k Ò v 8 â ' k ' 8 â ' ož

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.

Ã w] Ô .

PIN1 ÖAnode

PIN 2 ÖCathode

PIN 3 ÖAnode

, M V / Marking

• - ~^a ¢ož

See Marking Instructions.

④ × ? d / Absolute Maximum Ratings(Ta=25 ;)

@ f Parameter	... Z Symbol	f > Rating	% y Unit
Peak Repetitive Reverse Voltage	V _{RRM}	200	V
Working Peak Reverse Voltage	V _{RWM}	200	V
Average Rectified Output Current @60Hz sine wave,R-load, Ta=25	I _O	20	A
Non-Repetitive Peak Forward Surge Current	I _{FSM}	150	A
Current Squared Time @1ms 0 t<8.3ms Tj=25	I ² T	94	A s
Thermal Resistance Junction to Case	R _{Jc}	2.0	/W
Junction Temperature Range	T _j	175	
Storage Temperature Range	T _{stg}	-55 175	

④ × ? d / Electrical Characteristics(Ta=25 ;)

@ f Parameter	... Z Symbol	y i Ú ^ Test Conditions	Â 4 > Min	Á ° > Typ	Â Ý > Max	% y Unit
Forward Voltage	V _F	I _F =10A(T _j =25)			0.95	V
Instantaneous Reverse Current	I _R	V _R =200V(T _j =25)			0.1	mA
		V _R =200V(T _j =125)			20	mA

Ô ? d • Ž ¢ / Electrical Characteristic Curve

Ø □ =) ¢ / Package Dimensions

Dimensions in millimeters (1mm =0.0394")

, M y f / Marking Instructions

BR
CT ****
MBR20200

^a ¢ y
(8 y , [W A
3 (8 y ° Z W A
) : Ä B È ã
y ÿ D Z W A k š Ÿ D Z J

Note:
BR: Company Code
MBR20200 y Product Type Code
CT: Internal Structure
****: Lot No. Code, code change with Lot No

